



1.0 STORAGE

1.1 Valves must be stored in accordance with BS3574— Recommendations for the Storage of Vulcanised Rubbers

2.0 INSTALLATION

2.1 Maximum tightening torque when fitted to 0.3–1.0mm thick fabric is 27Nm (20lb.ft). This torque has to be de-rated to 20Nm (15lb.ft for fabric at the maximum recommended thickness of 3.0mm). Valve assembly should be re-torqued after at least 12 hours.

2.2 Special adaptors are available to enable standard 1/2" drive equipment to be used to tighten the valve assembly. Part No. TM672 mates with the body. Part No. C14898 mates with the housing.

2.3 The Sealing Plug, Sealing Cap (Screw On Type) and Skirt are available separately.

2.4 Various opening & reseal pressures are available. Please see selection chart.

2.5 It is the users responsibility to ensure that any fluids used during installation or operation are compatible with this valve.

3.0 SERVICING

3.1 There are no user serviceable parts in the assembly.

3.2 If it is necessary to clean the valve only use household detergent and warm water. Do not use solvent cleaners.

For further information please contact
Leafield Marine Limited

INSTRUCTION SHEET FOR
PRESSURE RELIEF VALVE
A10 STANDARD

DRAWING No.
14921

REVISION
E

SHEET 1
OF 1